

SEAM THICKNESS

DDH.	B	C	C'	D	E
6404	48 1/2 ^{DC} (32 1/4)	36	28 ⁵	0	26
6303	56 1/2 ⁴⁴ (31 1/2)	5	25 1/2	9	34 1/2
6301	46 1/4 ^{41 1/4}	24	12	0	34 1/4
6408	53 3/4 ^(32 1/4)	—	—	—	—
6411	38 1/4 ^(37 1/2)	—	—	—	—
6413	35 ^{DC}	—	—	—	—
6405	48 1/2 ^{DC} (31)	—	9	15	13
6406	36 3/4 ^(28 1/2)	—	13 ^{DC}	29 1/2	16
6407	57 1/2 ^{DC} (33 1/4)	—	—	—	—
6417	59 1/2 ^{DC} (31)	—	—	26 ^{DC}	50 ^{DC}
6412	35 ^{DC} (23)	—	—	30	38
6302	47 ¹⁹ (36)	24 3/4	—	34	43
6409	60 ^{BC on top} (30)	—	D.C.	—	41 3/4
6416	29	26 ^{DC}	41 ^{DC}	21	23 1/2

Directly West of Amsbry "E" seam mine developed 1000' and hit fault.
DDH 500'± ahead of face in fault.

E E D C' C B

DDH #	E	E	D	C'	C	B
23	—	—	—	2'-9"	47	2'-5" 25'-6"
25	2'-11"	77	0-6"	46	1'-7"	—
26	3'-2"	33	0-8"	40	0-5"	38 0-10"
36	2-3"	65	1-0"	49	2-2 1/2"	—
9	0-9"	47	split	—	—	—