



I.D. 36-07300 Person Responsible

VENTILATION LEGEND

INTAKE AIR	RETURN AIR
PRIMARY ESCAPEWAY	ALTERNATE ESCAPEWAY
PERMANENT (CEMENT BLOCK) STOPPING	TEMPORARY (CANVAS) STOPPING
REGULATOR	OVERCAST
PERMANENT STOPPING WITH DOOR	BELT HAULAGE
REDUCED AIR FLOW	AIR LOCK DOOR
	AIR READING
	BLEEDER EVALUATION POINT

Subsidence Legend

M.A.P. No. 56841327

Contemplated Mining From To

Amendment Area	Dwelling Constructed Prior To April 27, 1966	Dwelling Constructed After April 27, 1966
Minimum Plan For Protected Structures	50% Mining Area	50% Mining Area
Previous Six Month's Mining		
Mining Completed		

Definitions of Abbreviations, Symbols, Etc. Used in Formulas & Examples:

SA = Support Area Under Protected Structure From Which Only 50% Of Coal Is Extracted

LD = Additional Support Added On Each Down-hill Side Of Support Area (Required If Structure Is Located On Terrace Or Slope Greater Than 5%)

D = Depth Of Cover Of Overburden

L = Length Of Structure

W = Width Of Structure

27 = Tangent Of 15 Degrees

15 FEET Safety Factor

RECEIVED JUL 27 1993
Dept. of Environmental Resources
McMurry District Office

PREPARED FOR
J & D MINING, INC.

MILLER RUN NO. 2 MINE R.D. 1 Central City
UPPER KITTANNING COAL SEAM Pa. 15926

SITUATE
SHADE TWP., SOMERSET CO., PENNSYLVANIA

SCALE: 1" = 100'

DATE: JUL 23 1993

PREPARED BY
MUSSER ENGINEERING
RD No. 1, Box 463, Central City, Pennsylvania 15926, 814/754-8477

FINAL MAP
All Mining ceased June 08, 1993