

February 1, 1955
 Safety Zone
 All mining will comply with the following:
 1. Shores not more than 30 feet wide.
 2. Cross surface not more than 18 feet wide.
 3. All pillars between shores of road or foot by road feet.
 4. No pillars more than 18 feet wide.
 5. No pillars more than 18 feet wide.
 6. No pillars more than 18 feet wide.
 This zone is 25 miles across. The distance in between is 25 miles. The distance in between is 25 miles. The distance in between is 25 miles.

February 1, 1955
 Safety Zone
 All mining will comply with the following:
 1. Shores not more than 30 feet wide.
 2. Cross surface not more than 18 feet wide.
 3. All pillars between shores of road or foot by road feet.
 4. No pillars more than 18 feet wide.
 5. No pillars more than 18 feet wide.
 6. No pillars more than 18 feet wide.
 This zone is 25 miles across. The distance in between is 25 miles. The distance in between is 25 miles. The distance in between is 25 miles.



HIRAM SWANK'S SONS
 MINE NO. 23
 SITUATED IN
 CONEMAUGH TWP., SOMERSET CO., PA.
 SCALE: 1"=100' TRACED FEB. 1, 1955

Safety Zone
 All mining will comply with the following:
 1. Shores not more than 30 feet wide.
 2. Cross surface not more than 18 feet wide.
 3. All pillars between shores of road or foot by road feet.
 4. No pillars more than 18 feet wide.
 5. No pillars more than 18 feet wide.
 6. No pillars more than 18 feet wide.
 This zone is 25 miles across. The distance in between is 25 miles. The distance in between is 25 miles. The distance in between is 25 miles.