FIT TO C-212

CLARKSVILLE BORO

A. TURNER

CLYDE No.2
MINED OUT

BURSON FAN

BURSON NO. 2 AIRSHAFT - RETURN - 21.0' DIA.
DEPTH 112.84' - TOP EL. 809.0' / BOTTOM EL. 696.16'
NO. 2 FAN JEFFERY 8H-111" AERODYNE
111" DIA. BLADE SETTING - FIXED, 525 RPM'S
100,800 CFM / PITOT TUBE AT FAN, 0 % CH_4
2.1" WATER GUAGE, PULLING 30 AMPS
FAN MOTOR
GENERAL ELECTRIC, 2300 VAC, 3PH, 200 HP, 30 AMPS
SPARE FAN MOTOR
ALLIS-CHALMERS, 2300 VAC, 3PH, 200 HP, 49.2 AMPS

CLYDE MINE
I.T.E.C.
I.D. No. 36-00967
VENTILATION REVIEW No. R-1

LEGEND

- TRACK
- BELT
- BELT HEAD
- BELT BLEEDER
- CHECK
- REGULATOR
- STOPPING
- STOPPING W. DOOR
- OVERCAST
- BELT AIR
- PANEL RETREAT MINING COMPLETE
- SAFETY OR PARTIAL MINING ZONE
- INTAKE
- RETURN
- INTAKE ESCAPEWAY
- RETURN ESCAPEWAY
- PROPOSED STOPPING
- PROPOSED INTAKE
- PROPOSED RETURN
- PROPOSED OVERCAST
- INTAKE SHAFT
- RETURN SHAFT
- STOPPING W/BLOCK RMVD
- B-6 BLEEDER STATION
- ROOF FALL

MINE POOL ELEVATION 696.0 FT.
DATE 11/10/92 EXTENDED SURVEY 12/24/92
DRN BY: R. PULIG

NOT FOR PUBLIC