

REQUIRED LIST

|                                    |                                                                                                                                                                                                                                                                   |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 201.0<br>271                       | Sta. 14+95<br><del>180</del> L.F. 21" Trip. Str. V.C. Pipe<br><del>505</del> C.Y. Cl. 2 Exc. (As Directed)<br>Pipe shall be laid level and to elevation shown on X-Sections.                                                                                      |
| 24<br>51.4<br>8.6                  | Sta. 18+65<br><del>180</del> L.F. 18" D.C.C. Pipe<br><del>505</del> C.Y. Cl. B Conc. (Edw. Lt.)<br><del>505</del> C.Y. Cl. 2 Exc. (Pipe)<br><del>505</del> C.Y. Cl. 2 Exc. (Edw.)<br><del>505</del> C.Y. Cl. 2 Exc. (Outlet)                                      |
| 13.1                               | Sta. 18+70 to Sta. 21+00 Lt.<br>Parallel Ditch<br><del>505</del> C.Y. Cl. 1 Exc. (Widening)<br><del>505</del> C.Y. Cl. 2 Exc.                                                                                                                                     |
| 100<br>2.3<br>2105<br>10.8<br>25.2 | Sta. 21+00<br><del>180</del> L.F. 18" D.C.C. Pipe<br><del>505</del> C.Y. Cl. B Conc. (Edw. Lt.)<br><del>505</del> C.Y. Cl. 2 Exc. (Pipe)<br><del>505</del> C.Y. Cl. 2 Exc. (Edw.)<br><del>505</del> C.Y. Foreign Borrow Excav. (Rock)<br>At discharge end of Pipe |
| 100<br>12<br>52.1<br>50            | Sta. 23+50<br><del>180</del> L.F. 18" D.C.C. Pipe<br><del>505</del> C.Y. Cl. B Conc. (Edw. Lt.)<br><del>505</del> C.Y. Cl. 2 Exc. (Pipe)<br><del>505</del> C.Y. Cl. 2 Exc. (Edw.)<br><del>505</del> C.Y. Cl. 2 Exc. (Outlet)                                      |
|                                    | Sta. 26+85 Lt.<br>Doad (18' Wide)<br><del>505</del> C.Y. Cl. 1 Exc.                                                                                                                                                                                               |
| 78<br>12<br>81.0<br>4.3            | Sta. 27+00<br><del>180</del> L.F. 18" D.C.C. Pipe<br><del>505</del> C.Y. Cl. B Conc. (Edw. Lt.)<br><del>505</del> C.Y. Cl. 2 Exc. (Pipe)<br><del>505</del> C.Y. Cl. 2 Exc. (Edw.)<br><del>505</del> C.Y. Foreign Borrow Excav. (Rock)                             |
|                                    | Sta. 14+48 to Sta. 16+93<br>6814 Cu Yds Foreign Borrow Excav. (Rock)<br>To fill stripping hole shall be placed as directed and as indicated on the plan and X-Sections.                                                                                           |
| 895                                | Sta. 21+54 to Sta. 22+98<br><del>505</del> Cu Yds Foreign Borrow Excav. (Rock)<br>To fill reservoir shall be placed as directed and as indicated on the X-Section.                                                                                                |

