



M10
 1' clay
 28' Brkn ref.
 18' s.s. gray
 5' tan
 31' gray
 1' Burat rock
 45' s.s. gray
 115' Broken
 2' Slate
 2' Bot. rock
 268'

M12
 285'
 20m 11/70
 38m 25/70

M10
 268'

3/15/70 checks measurements

STRIPPING
 BACKFILLED WITH
 BREAKER REFUSE

SF5
 4' clay bank
 23' Breaker
 13'
 42'
 40.5'
 67.4'
 82.0' Blocked

B9 222'

PROPOSED
 1/2:1 = LINE OF BACKFILL

B9
 9' clay bank
 21' Brkn ref.
 10' shale burat reddish
 4' s.s. light gray
 14' broken
 7' hard gray
 6' light
 34' broken
 11' shale hard reddish gray
 3' conglomerate, hard gray
 22' check
 3' gray
 4' slate dark gray
 34' shale gray
 40' broken
 4' Bot. slate
 222'

124° 110°
 130° 124°
 150° 138°
 150° 138°
 162° 128°
 143° 126°
 143° 126°
 116° 110°
 114°
 110°
 110°
 316° 143°
 346° 354°
 387° 406°
 435° 436°
 467° 462°
 472° 478°
 411° 471°
 406° 461°
 414° 423°
 372° 371°
 357° 361°

496°
 548°
 534°
 511°
 494°
 487°
 482°
 526°
 548°
 548°
 551°
 561° at 222'

WATER LEVEL 1060
 WATER LEVEL 1044

P.B.K. & L. CO.
 GIRARD ESTATE

M12
 4' clay
 9' Brkn ref.
 5' shale
 5' s.s.
 115' s.s. gray
 2' slate
 2' coal
 2' slate
 11' s.s. tan
 8' shale
 53' s.s. gray
 10' dark
 17'
 3' Brkn
 42' broken
 288'