FORM 6

I.D.No. _____

Borehole Number: TB-10
Surface Elevation (Ft/MSL): 1698.52' (ft)
Borehole Diameter: 6" inches, From 0.0' To 40.5'
3 1/2" inches, From 40.5' To 189.0'
Total Depth: 189.0' (ft)
Depth to Static Ground Water Level (SWL): 49.0' (ft)
Date SWL Measured: 1/19/90 (mm/dd/yy)

Drilling Method: HOLLOW STEM AUGER & NX WIRELINE
Date Drilled: 1/17/90 - 1/19/90 (mm/dd/yy)
Drilled By: HETAGER DRILLING CO.
Drillers License Number: 1728
Logged By: MJG
County: JEFFERSON COUNTY
Township or Municipality: PINE CREEK

Depth (Ft)	Lithologic Description	Plot	Ground Water* Observations	Samples No.	Samples Rec.** & Att.	Comments	Well/Piezometer Construction	Depth (Ft)
0	(MINE SPOIL)-MEDIUM STIFF, GRAY-BROWN CLAYEY SILT, SHALE FRAGMENTS, CARBONACEOUS, TRACE OF SANDSTONE FRAGMENTS			1	18/18	DRY-MOIST		0
5				2	18/18			5
10				3	12/18			10
15				4	15/18			15
20				5	16/18			20
25				6	11/18			25
30				7	16/18			30
35				8	15/18			35
40	40.0'			9	12/18	DRY-DAMP		40
45	SOFT, GRAY CLAYSTONE, WEATHERED 43.5'					LOST WATER AT START OF CORE		45
50	MEDIUM HARD, GRAY, SANDY CLAYSTONE, UNBROKEN TO BROKEN 49.0'		▼	1	8.5'/ 8.5'	OPEN FRACTURES WITH IRON STAINING		50
55	MEDIUM HARD, GRAY, INTERBEDDED SHALE AND FINE GRAINED SANDSTONE, UNBROKEN TO BROKEN			2	9.8'/ 10.0'			55
60								60

* ▽ Encountered Ground Water ▼ Composite Static Water Level **Recovered/Attempted

F-256
SLW 2/15/91

Use additional sheets with this format as necessary

②